

This list specifies the components of insulating glass units which are subject to a quality assurance according to RAL-GZ 520/2 "General and Specific Quality and Inspection Regulations for Components of Insulating Glass Units" and thus may be used for the production of quality-marked insulating glass units according to RAL-GZ 520. The inclusion in this list says nothing about other properties of the components which are not subject of quality the assurance according to RAL-GZ 520/2. For information about further properties, other documents such as material safety data sheets etc are to be consulted.

Spacers

Manufacturer	Gr. ¹⁾	Product	Cat. ²⁾	Rem. ³⁾
Edgetech Europe GmbH	Group	Super Spacer [®] T-Spacer [™] Premium	Е	
		Super Spacer [®] T-Spacer [™] Premium Plus	E	
		Super Spacer [®] T-Spacer [™] SG	E	
		Super Spacer [®] TriSeal TM Premium Plus	E	
Fenzi Group	•	Butylver TPS	D	
HELIMA GmbH		ALUTEC	Α	
		NIROTEC	A	
Kömmerling Chemische Fabrik GmbH		Ködispace	D	
		Ködispace 4SG	D	
Profilglass S.P.A.		Alu-Abstandhalter biegsam Serie 3000,	А	
		H6,5mm PGE, 6,5mm PGS		
ROLLTECH A/S (Alupro)		Multitech G	С	
	Group	Chromatech	A	
		Chromatech plus	Α	
		CHROMATECH ultra F / F1	В	
		CHROMATECH ultra S	В	
	Group	Aluminium Profil H65 (Alupro)	Α	
		Ferrotech (2WS)	А	
		Thermix TX Pro	В	
Technoform Glass Insulation GmbH	Group	Technoform-Spacer SP12 (TGI Spacer M 8 mm)	В	
		Technoform-Spacer SP13 (TGI Sp.M w/o wire)	В	
		Technoform-Spacer SP14 (TGI Sp.M with wire)	В	
		Technoform-Spacer SP18	В	
		Technoform-Spacer SP16 (TGI Sp. Precision)	С	
Vetrotech Saint-Gobain (Int.) AG	I & I	Swisspacer Advance	С	
		Swisspacer Ultimate	С	
		Swisspacer Ultimate Pro	С	

Status: April 4th, 2024 Page 1 of 4



Desiccants

Manufacturer	Gr. ¹⁾	Product	T _{c,min} ⁵⁾ [%]	Rem. ³⁾
Arkema France	ədc	Siliporite NK30 B0.7	16,5	
	Gruppe	Siliporite NK30 B1.3	16,5	
eco in sp. z o.o.		eco mol	16,5	
Fenzi Group		Molver MGM 01	16,3	
Grace GmbH		Phonosorb 551 [®]	16,5	
	Gruppe	Phonosorb 555®	16,5	
	٥	Phonosorb 558 [®]	16,5	
Nedex Chemie Deutschland GmbH		Zeolan K	16,5	
		Nanomol-C	17,2	
Rottler und Rüdiger und Partner GmbH		RR sorb	16,5	
Schollglas		GEWEsorb	16,5	
Shandong Natergy Energy Technology Co., Ltd		Natergy sieve 3A	16,5	b)
Tenachem SIA		TENASIEVE	16,5	b)

Primary Sealants

Manufacturer	Product	Rem. ³⁾
ECI European Chemical Industries LTD	Emcepren 80 IG	
	Emcepren 80 IGS	
eco in sp. z o.o.	eco butyl	
Fenzi Group	Butylver	
	Butylver GB	
	Butylver SS	
	Butylver XL	
IGK Isolierglasklebestoffe GmbH	IGK 511	
	IGK 511 HT	b)
Kömmerling Chemische Fabrik GmbH	GD 115	
	GD 115 S	
	GD 115 S-LV	
	Naftotherm BU-S	
Tenachem SIA	TENAGLASS 3	
	TENAGLASS-PIB	
Tremco CPG Germany GmbH	Tremco JS680	
	Tremco JS780 S	

Status: April 4th, 2024 Page 2 of 4



Secondary Sealants

Manufacturer	Product	Cat. ⁴⁾	Rem. ³⁾
Dow Silicones Deutschland GmbH	DOWSIL 3362	SI	
	DOWSIL 3363	SI	
	DOWSIL 993	SI	
ECI European Chemical Industries LTD	Emcepren 200	PU	
	Emcepren 200 neo	PU	
	Emcepren 200 classic	PU	
eco in sp. z o.o.	Eco pur CBD	PU	
	Eco pur C	PU	
Fenzi Group	Poliver GP-AC	PU	
	Poliver AC	PU	
	Poliver F	PU	b)
	Thiover	PS	
	Thiover F	PS	
IGK Isolierglasklebestoffe GmbH	IGK 130	PU	
	IGK 330	PS	
Kömmerling Chemische Fabrik GmbH	GD 116	PS	
	GD 116 LV	PS	
	GD 116 NA	PS	
	Naftotherm M 82-935	PS	
	GD 677 NA	PU	
	GD 677 NA plus	PU	
	GD 920	SI	
Sika Engineering Silicones srl	Sikasil IG-25 HM Plus (2K Si)	SI	
	Sikasil SG-500 (2K Si)	SI	
Tenachem SIA	TENAGLASS PU BE	PU	
	TENAGLASS PU FR S	PU	
	TENAGLASS PS EN	PS	
Tremco CPG Germany GmbH	Tremco JS440	PU	
	Tremco JS450	PU	

Status: April 4th, 2024 Page 3 of 4



1) Explanation "Group"

Under certain conditions, the components 'Spacers' and 'Desiccants' can be combined to groups. From one product group, at least one representative product per manufacturer must be sampled half-yearly and forwarded for inspection. (For more information about grouping please see Quality and Inspection Regulations for Components, section 2.1 resp. 3.1).

²⁾ Spacer categories acc. to Specific Quality and Inspection Regulations for Spacers, Section 2.1

- A = Hollow spacers in aluminium, galvanized steel or stainless steel
- B = Hollow spacers made of composite materials with metallic adhesion surface to the sealants
- C = Hollow spacers made of composite materials with non-metallic adhesion surface to the sealants
- D = On site, hot applied flexible spacer (Thermoplastic material)
- E = Prefabricated foamed spacer profiles from the roll

3) Remarks

- a) An inspection contract has been concluded with a testing and inspection body, the Technical Documentation has been submitted in full, and the initial visit for sampling has already taken place. The test report is not yet available.
- b) The test report of the initial visit has been submitted. Continuous monitoring reports are not yet available.

4) Secondary sealants

- PU = Secondary sealant on the basis of Polyurethane
- PS = Secondary sealant on the basis of Polysulfide
- SI = Secondary sealant on the basis of Silikone

5) Tc,min (Minimum value of Standard moisture adsorption capacity

The Tc,min-value was introduced in accordance with the decision of the Quality Committee for insulating glass units on November 8th, 2022. Unless a desiccant manufacturer declares a different value for his product, the Tc,min-value is set at 16.5 %. Since January 2023, the Tc,min-value is used by the testing and inspection bodies to calculate the I-index in short climate tests as part of the quality monitoring of insulating glass units. As part of the quality monitoring of components of insulating glass units, the Tc,min-value is monitored in addition to the existing specifications of the Quality and Inspection Regulatoins for desiccants. If the Tc,min-value declared on this list is not reached, the periodic test/inspection is failed.

Status: April 4th, 2024 Page 4 of 4